

GAS - APPLIANCE - WATER

Airgaps



PRECISION
INSTALLATION
PRODUCTS

DISHWASHER AIRGAP - IMPORT



PART NUMBER

AG5P

ITEM DESCRIPTION

ECONOMY DW AIRGAP W/ POLYPROPYLENE BODY AND CHROME PLATED PLASTIC CAP

REPLACEMENT AIRGAP COVER - UPC, IPC, NSF



PART NUMBER

AGAP-COVER-ORB

ITEM DESCRIPTION

AIRGAP COVER - OIL RUBBED BRONZE

AGAP-COVER-SS

AIRGAP COVER - BRUSHED STAINLESS

DISHWASHER & RO AMERIGAP™



PART NUMBER

AT52-RO

ITEM DESCRIPTION

AMERIGAP 3-PORTED AIRGAP W/ 1/4" JG DRAIN - CODE APPROVED

Description

One inlet port accepts standard dishwasher hose (5/8" I.D.). Other small flow inlet port comes with quick connect type fitting that accepts 1/4" O.D. poly tubing from an undersink RO unit. Eliminates the need for an RO air gap faucet and also the illegal metal screw drive clamp. UPC®, IPC and NSF.

GAS - APPLIANCE - WATER Airgaps

DRAIN BOA™



<u>PART NUMBER</u>	<u>ITEM DESCRIPTION</u>
AT52-RO	AMERIGAP 3-PORTED AIRGAP W/ 1/4" JG DRAIN - CODE APPROVED

Description

Inlet port directly accepts 3/8" and 1/2" O.D. poly tubing. Dual plumbing code listed sink tailpiece fitting. Comes with 2 plastic clamps and a stainless steel screw drive clamp as shown. Comes with a metal worm clamp for securing tubing to small port. UPC® and NSF.

DISHWASHER AIRGAP - EASTMAN



<u>PART NUMBER</u>	<u>ITEM DESCRIPTION</u>
DAGE-EA	EASTMAN PLASTIC AIR GAP - BOX - METAL CHROME CAP

Description

Blue body with brushed nickel cap. For Dishwasher & Disposer installation. UPC®.

EASTMAN / EZ-FLO REPLACEMENT AIRGAP PARTS ONLY



<u>PART NUMBER</u>	<u>ITEM DESCRIPTION</u>
AGOCCP	EZ-FLO/EASTMAN CHROME PLATED AIR GAP OUTER CAP
AGOCBN	EZ-FLO/EASTMAN BRUSHED NICKEL AIR GAP OUTER CAP
AGPIC	EZ-FLO/EASTMAN PLASTIC INNER CAP FOR AIRGAP
AGPSW	EZ-FLO/EASTMAN PLASTIC SPACER WASHER FOR AIRGAP
AGRW	EZ-FLO/EASTMAN RUBBER WASHER FOR AIRGAP

GAS - APPLIANCE - WATER

Airgaps



GAP-A-RO: 31-S (KIT S-A)



PART NUMBER

ITEM DESCRIPTION

AGAP-31S-A

AIRGAP GAP-A-RO 3/8" INLET X 3/8" OUTLET AIRGAP (CASE 50)

Description

Easy connection to inlet and outlet ports. Comes with 3/8" inlet and outlet ports. Unit designs lab tested at over 1/2 G.P.M. [2 Liter/minute] or more, depending on style of unit. Suggested usage approximately 1 to 16 oz/min. [30 to 500 ml/min]. Vertical wall mounting bracket and screws included. UPC®, IPC and NSF.

GAP-A-RO: 31-S (KIT S-B)



PART NUMBER

ITEM DESCRIPTION

AGAP-31S-B

AIRGAP GAP-A-RO 1/4" INLET X 3/8" OUTLET AIRGAP

Description

Easy connection to inlet and outlet ports. Comes with 1/4" inlet and 3/8" outlet ports. Unit designs lab tested at over 1/2 G.P.M. [2 L/min] or more, depending on style of unit. Suggested usage approximately 1 to 16 oz/min [30 to 500 ml/min]. Vertical wall mounting bracket and screws included. UPC®, IPC and NSF.

GAP-A-RO: 31-S (KIT S-C)



PART NUMBER

ITEM DESCRIPTION

AGAP-31S-C

AIRGAP GAP-A-RO INLINE AIRGAP WALL MOUNT

Description

Easy connection to inlet and outlet ports. Provides compact air gap unit and convenient mounting arrangement for RO type water coolers. Unit designs lab tested at over 1/2 G.P.M. [2 L/min] or more, depending on style of unit. Suggested usage approximately 1 to 16 oz/min [30 to 500 ml/min]. Vertical wall mounting bracket and screws included. UPC®, IPC and NSF.

GAP-A-RO:31-S KIT(S-D)



PART NUMBER

ITEM DESCRIPTION

AGAP-31S-D

AIRGAP GAP-A-RO SINK MOUNT 1/4" INLET X 3/8" OUT

Description

Easy connection to inlet and outlet ports. Provides a convenient alternative to include a code listed air gap unit in the indirect drain piping; if a dispensing faucet is not needed or is to be remotely located or if installer prefers not to use an air gap style dispensing faucet. Unit designs lab tested at over 1/2 G.P.M. [2 L/min] or more, depending on style of unit. Suggested usage approximately 1 to 16 oz/min. [30 to 500 ml/min]. Mounts on top of sink. UPC®, IPC and NSF.

GAS - APPLIANCE - WATER

Airgaps

GAP-IT: 61-D (KIT HF1)



PART NUMBER

AT52-RO

ITEM DESCRIPTION

AMERIGAP 3-PORTED AIRGAP W/ 1/4" JG DRAIN - CODE APPROVED

Description

Designed to fit into recessed washing machine outlet boxes w/ 2" standpipes. Fits onto top of exposed 2" standpipes. Units feature a flow straightener to quiet and smooth out turbulent flow and splatter shields to eliminate any water droplets that may splatter out of either air gap opening. Units designed to allow space for washer drain hook or soft rubber washer hose to share standpipe with Gap-It. Multiple air gap openings exceed the code mandated minimum of at least one (1)" vertical opening. Comes with mounting base for 2" pipe. UPC®, IPC and NSF.

GAP-IT: 61-S (KIT HF2)



PART NUMBER

AGAP-612

ITEM DESCRIPTION

AIRGAP GAP-IT INLINE HIGH FLOW AIRGAP FOR 1-1/2" PIPE

Description

Designed to fit into recessed washing machine outlet boxes w/ 1 1/2" standpipes. Units feature a flow straightener to quiet and smooth out turbulent flow and splatter shields to eliminate any water droplets that may splatter out of either air gap opening. Units designed to allow space for washer drain hook or soft rubber washer hose to share standpipe with Gap-It. Multiple air gap openings exceed the code mandated minimum of at least one (1)" vertical opening. Comes with vertical wall mounting bracket and screws. UPC®, IPC and NSF.

MR.DRAIN



PART NUMBER

AMD-10A

ITEM DESCRIPTION

AIRGAP MISTER DRAIN AIRGAP USED WITH STANDPIPE

Description

Fits 1 1/2" or 2" standpipes. Unit housing length approx. 5 1/2" (13.97 cm). Recommended usage 1 to 7 gal/min (3.7 to 26.5 L/min). Tested at 15 gal/min (56.8 L/min). Allows soft rubber washer hose or washer metal drain hook to share standpipe with other Air Gap units. Inlet port fits 1/2" SCH 40 PVC slip fittings or special couplings. Provides more than twice the code-required minimum air gap opening. Can be mounted at 3 different levels. UPC®, IPC and NSF.

GAS - APPLIANCE - WATER

Airgaps



GAP-CAP



<u>PART NUMBER</u>	<u>ITEM DESCRIPTION</u>
AGAP-CAP	AIRGAP GAP-CAP-MODEL 8500- MOUNTS ON 1-1/2" - 2" PIPE (METAL OR PLASTIC)

Description

Ideal space-saving air gap. Twin inlet port: Larger port is 1/2" slip that also directly accommodates 5/8" O.D. poly tubing. Smaller RO port directly accepts 3/8" O.D. poly tubing. Includes inlet elbow with flow straightener 5 to 7 gal/min. Fits 1 1/2" & 2" standpipes. UPC®, IPC and NSF.

DUAL BARB ELBOW



<u>PART NUMBER</u>	<u>ITEM DESCRIPTION</u>
AG170-008	AIRGAP DUAL BARB ELBOW - FITS 1/2" & 5/8" ID POLY TUBE - FITS THE AMD-10A & AGAP-CAP

Description

Fits Mr. Drain and Gap-Cap™ units.

GAP-A-DRAIN UNIVERSAL AIRGAP



<u>PART NUMBER</u>	<u>ITEM DESCRIPTION</u>
AG180-002	AIRGAP GAP-A-DRAIN UNIVERSAL AIRGAP - FLOOR DRAINS, 2" AND 1-1/2" STAND PIPES

Description

Fits 1 1/2" stand pipe with reducer or 2" standpipes. Accommodates discharge rates of up to 35 gal/min. Design lab tested at 15 gal/min. Fits up to three 3/4" PVC or copper drain pipes and two Mr. Drains. Provides required airgap to comply with ASME standard. Easily attaches to floor drains using metal hook (included) Can be mounted on floor drain, 2", and 1 1/2" stand pipes. UPC®, IPC and NSF.

GAS - APPLIANCE - WATER Airgaps

GAP-A-FLO



PART NUMBER

AGAF-211

ITEM DESCRIPTION

AIRGAP GAP-A-FLO INLINE AIRGAP WITH MALE & FEMALE THREADS

Description

Unit approximately 8" long. Provides an in-line air gap, usually installed in the last 5 ft (1.5 meters) of the indirect drain piping and must be in the down leg of the drain line piping. Unit can be tilted at any angle (down as low as 45° angle) when installing if needed, (window opening on top side). Molded clamp groove plus included "Jiffy Clip" enable easy vertical wall mounting. Unique design incorporates a rotatable splash guard/splatter shield, to eliminate splatter of water droplets out of either air gap opening. Multiple air gap openings far exceed the code mandated minimum of (1)" vertical. All noted threads are American NPT threads. Unit design lab tested at 15 gal/min (56.8 L/min). Recommended usage up to 7 gal/min (26.5 L/min). UPC®, IPC and NSF.

HYDROTECH AIRGAP



PART NUMBER

AG3001

ITEM DESCRIPTION

HYDROTECH WALL MOUNTED AIRGAP